



WASHING MACHINE FOR FULL CONTAINERS GG16

Washing machine, completely made of Aisi 304 stainless steel. Version with 3 phases: washing, rinsing and draining – Version with only two phases, washing and draining, also available (**mod. GG08**)



APPROX. TECHNICAL DATA

- containers : max Ø 200mm – max H. 300mm
- Air consumption : 5 NI/1» at machine start, pressure 6 bar
- Installed power : 6 kW
- Steam consumption : 100 kg/h
- Dimensions : 6000x700
- Working height : 1000 ±50 mm

This technical sheet gives an approximate description of the machine.

The technical features and the machine configuration are to be confirmed at the time of order.

- First phase: washing section consisting of nozzle-supporting pipes fed by a pump. The washing water is stocked in a tank.
- At the end of the first phase, the product is roughly dried by a blower. The second section is also provided with nozzle-supporting pipes for rinsing purposes, also fed by a pump which pours water from an underneath tank.
- Both tanks can be heated by steam to waste
- Third phase: final draining by four blowers powered by a 3kw motor
- Independent adjustment of the water contained in the two tanks by two manually adjustable thermostats.
- Fit for the aspiration of the vapours produced during the washing phases.
- The machine conveyor is controlled by variable frequency drive with a special design to ease the passage of as much water as possible.
- Equipped with electric control cabinet with low-voltage controls and IP65 protection